ANNIE SLOAN - CHALK PAINT® LACQUER

PRODUCT INFORMATION SHEET

PRODUCT OVERVIEW

- Annie Sloan Chalk Paint® Lacquer is a hard-wearing water based polyacrylic varnish.
- Designed specifically for use with Chalk Paint®.
- · Thicker formula helps prevent drips and runs during application.
- · Available in 750ml (25oz) tins.
- · Built in UV protection to keep colors vibrant outdoors.

- · Choice of Matt and Gloss finishes.
- · Suitable for indoor and outdoor use.
- · Abrasion resistant.
- · Low in VOC's (<50g per litre).
- · Certified as Toy Safe (EU Toy Safety Directive BS EN 71-3:2013).



GLOSS

MATT

COVERAGE

Annie Sloan Chalk Paint® Lacquer comes in 750ml (25oz) tins One tin will cover 19 square metres (204ft 2).

Touch dry in 30 minutes.

Recoat in 1-2 hours (temperature and humidity dependent). Curing time for maximum protection occurs over 14 days.

PREPARATION

Ensure surface is dry and dust free before you begin.

Do not apply over waxed surfaces.

Always test an area of paint and lacquer before you begin as results can vary depending on previous treatment.

APPLICATION

Always test first - this will save you time in the long run! Stir well before using and regularly during use.

Apply using a high quality brush or sponge/foam roller. Don't 'over brush' the Chalk Paint® Lacquer when applying. When using lacquer over Chalk Paint®, dilute the first coat. with 10% water for a more even finish.

Sand between coats for an extra smooth finish.

DRYING TIME/REAPPLICATION

A second coat can be applied in 1-2 hours but may take longer. Cooler temperatures and higher humidity will extend drying time. Leave to dry overnight before use.

Curing time for maximum protection occurs over 14 days.

EXTERIOR USE

Apply two thin coats, ensuring that every surface of your item is completely encapsulated to prevent water ingress, which can cause peeling or adhesion failure over time.

Store unused painted and lacquered pieces indoors or under cover over the winter to prolong the life of the finish.

CLEAN UP

Wash brushes or rollers in soap and water immediately after use.

AFTERCARE

Clean with a damp cloth using mild soapy water.

Avoid regular use of chemical cleaners.

Avoid exposure to steam and heat.

PRODUCT TIPS

Creative tip! Use Matt and Gloss Chalk Paint® Lacquers side by side to create textural contrast.

Apply Matt Lacquer sparingly to avoid cloudiness over dark colours.

Consider using a coat of Gloss first over a textured finish to avoid cloudiness.

For an extra durable Matt finish, use 1-2 coats of Gloss followed by a coat of Matt.

Apply using a sponge roller over intricate paintwork designs to avoid smudging.

Lacquer can be sprayed - experiment with dilution rates to see what works best with your particular model.

YELLOWING AND BLEED THROUGH

Annie Sloan Chalk Paint® Lacquer dries completely clear over non-reactive surfaces such as laminate or plastic. Wood surfaces can be unpredictable, however, and as with all similar water based products there is a possibility of the topcoat reactivating tannins, stains or other substances in the wood, causing the topcoat to yellow. This is most evident when working with light colors. Chalk Paint® Wax can be a less problematic finish on pieces where staining is likely to be drawn out by lacquer. Seal affected surfaces with shellac or appropriate primer.

STORAGE/ SHELF LIFE

Store in a cool and dry place, preferably at a constant temperature.

To maximize shelf life, decant used tins that are less than half full into smaller, tightly sealed containers.

For best results, use within year of purchase.

ANNIE SLOAN - CHALK PAINT® LACQUER

PRODUCT INFORMATION SHEET

PRECAUTIONARY STATEMENTS

Keep out of reach of children.

Avoid breathing vapour/spray.

Wear protective gloves.

If on skin, wash with plenty of water.

If ingested, rinse mouth thoroughly with water.

If in eyes, remove contact lenses and rinse thoroughly with saline or fresh water.

Seek medical attention if symptoms are severe or persist after washing.

May cause sensitisation or allergic reaction in sensitive individuals.

SDS INFORMATION AVAILABLE ON REQUEST email: enquiries@anniesloan.com

Disclaimer: Information and technical advice supplied by, or on behalf of, Annie Sloan Interiors cannot be construed to imply any legally binding assurance of any product's suitability for a specific purpose. Furthermore, any and all advice provided by employees of Annie Sloan Interiors, or by our stockists, regarding the use of our products is given in good faith and to the best of our current knowledge and experience. Advice is provided without warranty, as site specific conditions are beyond our control. Information supplied does not absolve users from the responsibility to carry out their own tests regarding suitability of the products for their intended purpose. @2019 ANNIE SLOAN INTERIORS LTD. 33 Cowley Road, Oxford OX4 1HP (+44)1865 770061.